KERN PCB10000-1

The standard in the laboratory





Measuring system	
Adjustment options:	External calibration
Eccentric loading at 1/3 [Max]:	300 mg
Linearity:	300 mg
Readability [d]:	100 mg
Recommended adjusting weight:	10 kg (F1)
Repeatability:	100 mg
Resolution:	100000
Stabilisation time under laboratory conditions:	3 s
Warm up time:	2 h
Weighing capacity [Max]:	10 kg
Weighing system:	Strain gauge
Weighing units:	tl (HK) tol g kg mo lb tl (Singap. Malays) dwt tl (Tw) ffa ozt oz

-1 -7	
Display digit height (large):	2,100 cm
Counting	
Counting resolution:	50000
Mininum piece weight at piece counting (Laboratory:	200 mg
Mininum piece weight at piece counting (Normal):	2 g

Display

Functions	
Counting function:	yes
Peak function:	yes
Percentage determination:	yes
Suspended weighing:	Hook
Vibration-free weighing (Animal weighing program):	yes

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	35 °C
Minimum ambient temperature:	5°C

Power supply	
Battery:	9 V Block
Charging time:	8 h
Input voltage:	100-240V AC 50/60Hz 0.5A
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	EURO CH US UK
Operating time:	20 h
Operating time (Backlight off):	48 h
Operating time (Backlight on):	24 h
Rechargeable battery:	Rchrg. battery optional


DAkkS Certificate:	963-128
Category	
Brand:	KERN
Category:	Balances
Product Group:	Precision balance

Services (optional)

Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	230 x 360 x 180 mm
Gross weight:	2,175 kg
Net weight:	1,660 kg
Shipping method:	Parcel service

Construction	
Casing material:	Plastic
Dimensions housing (WxDxH):	163 x 245 x 79 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Weighing surface (WxD):	150 x 170 mm

KERN PCB10000-1





Piktogramme

STANDARD



OPTION

